



**COOL SOLUTIONS
FOR PROFESSIONALS**




GCM012S AIR

3 STAINLESS STEEL GRIDS INCLUDED + runners


| | |
|------------------------------|--------|
| WATER-COOLED VERSION GCM012S | CAM 04 |
| CASTORS | RT-84 |
| REMOTE UNIT GCM012S | URM04 |

| | GCM012S |
|-----------------------------------|----------------|
| Dimensions (WxDxH) mm | 790x800x1320 |
| El. power supply (V/ph/Hz) | 230 / 1 / 50 |
| Input electric power (W) | 2000 |
| Max. absorbed current (A) | 9,2 |
| Refrig. Capacity (W) | 1300 |



**CAPACITY IN
GELATO TUBS**
360x165x120mm

12



**CAPACITY IN
GELATO TUBS**
360x250x120mm

8

GCM012S
BLAST-FREEZER
FOR GELATO

GENERAL FEATURES

- External sides and top in AISI 304 18/10 stainless steel th. 0.6mm (Scotch-Brite satin finish)
- AISI 304 18/10 stainless steel door th. 0.8mm (Scotch-Brite satin finish)
- Internal covering completely radiated in AISI 304 18/10 stainless steel
- Internal base moulded for containment with central drain connection for discharge of water
- High-density expanded polyurethane 60mm insulation (about 42 kg/m3), without HCFC
- Copper - aluminum evaporator, protected with non-toxic epoxy resins through cataphoresis
- Evaporator with multiple gas injection points
- Fan deflector can be opened on side hinges, in order to clean the evaporator
- Copper condensing coil with high heat yield aluminum fins
- Anti-condensation resistance positioned in the box under the magnetic gasket
- Ergonomic handle on the complete door length and magnetic gaskets on the 4 sides of the door
- Self-closing doors with block when opened to 100°
- Stainless steel feet Ø 2" height-adjustable H 150÷180 mm with anti-scratch cap
- Core probe heated for easy extraction

INTERNAL SET-UP

- Equipped with one set of tray slides supports (removable) having 11 positions with 50 mm. interstep and 17 positions at 32,5 mm. Interstep
- 3 pair of "C"-shaped guides and 3 stainless steel grids 600x400 + 5 pair of "L" shaped runners
- heated core probe

REFRIGERANT UNIT

- Fans with indirect flow onto the product
- Hermetic compressor
- R404A refrigerant liquid
- Evaporators with large exchange surfaces, for high efficiency
- Manual defrosting device and condensation evaporation system without use of electrical energy
- High capacity liquid/gas heat exchanger

**COMMANDS, CONTROLS AND
SAFETY DEVICES**

- Control and command circuit board equipped with high-visibility custom display,
- The T version can memorise up to 99 programs, can store any HACCP alarms in the memory and control up to 4 needle or 4 sensors (optional)
- Circuit breaker for compressor protection
- Internal fan stop micro switch when door is opened

OPTIONS / ACCESSORIES

- Version with remote unit
- Condensing unit with water cooling unit
- Revolving castors
- Printing kit
- Sterilizing kit with removable Sterilox