



**COOL SOLUTIONS
FOR PROFESSIONALS**



GDM006S

AIR

GCM006S

AIR

1 STAINLESS STEEL GRID INCLUDED + runners

WATER-COOLED VERSION GDM006S CAM02


WATER-COOLED VERSION GCM006S CAM03

CASTORS RT-64

REMOTE UNIT ON GDM006S URM 02

REMOTE UNIT ON GCM006S URM 03

	GDM006S	GCM006S
Dimensions (WxDxH) mm	790x700x850	
El. power supply (V/ph/Hz)	230 / 1 / 50	
Input electric power (W)	1200	1400
Max. absorbed current (A)	6,2	6,7
Refrig. Capacity (W)	690	810



**CAPACITY IN
GELATO TUBS** **6**
360x165x120mm



**CAPACITY IN
GELATO TUBS** **4**
360x250x120mm

GDM006S GCM006S

BLAST-FREEZER FOR GELATO

GENERAL FEATURES

- External sides and top in AISI 304 18/10 stainless steel th. 0.6mm (Scotch-Brite satin finish)
- AISI 304 18/10 stainless steel door th. 0.8mm (Scotch-Brite satin finish)
- Internal covering completely radiated in AISI 304 18/10 stainless steel
- Internal base moulded for containment with central drain connection for discharge of water
- High-density expanded polyurethane 60mm insulation (about 42 kg/m³), without HCFC
- Copper - aluminum evaporator, protected with non-toxic epoxy resins through cataphoresis
- Evaporator with multiple gas injection points
- Fan deflector can be opened on side hinges, in order to clean the evaporator
- Copper condensing coil with high heat yield aluminum fins
- Anti-condensation resistance positioned in the box under the magnetic gasket
- Ergonomic handle on the complete door length and magnetic gaskets on the 4 sides of the door
- Self-closing doors with block when opened to 100°
- Stainless steel feet Ø 2" height-adjustable H 150÷180 mm with anti-scratch cap
- Core probe heated for easy extraction

INTERNAL SET-UP

- Equipped with one set of tray slides supports (removable) having 6 positions with 50 mm. interstep and 10 positions at 32,5 mm. Interstep
- one pair of "C"-shaped runners and one stainless steel grid 600x400 + 4 pair of "L" shaped runners
- heated core probe

REFRIGERANT UNIT

- Fans with indirect flow onto the product
- Hermetic compressor
- R404A refrigerant liquid
- Evaporators with large exchange surfaces, for high efficiency
- Manual defrosting device and condensation evaporation system without use of electrical energy
- High capacity liquid/gas heat exchanger

COMMANDS, CONTROLS AND SAFETY DEVICES

- Control and command circuit board equipped with high-visibility custom display,
- The T version can memorise up to 99 programs, can store any HACCP alarms in the memory and control up to 4 needle or 4 sensors (optional)
- Circuit breaker for compressor protection
- Internal fan stop micro switch when door is opened

OPTIONS / ACCESSORIES

- Version with remote unit
- Condensing unit with water cooling unit
- Revolving castors
- Printing kit
- Sterilizing kit with removable Sterilox